
COMPLETEPre-Cut Kit

8X14 THREE SLED SHED

STORAGE SOLUTIONS



The heavy-duty sliding barn doors and wide pressure treated ramp provide three easily accessible entrances into this spacious storage shed. Many of our clients use this design to house their ATV's, snowmobiles, tractors, lawnmowers, and sports equipment.



COMPLETE PRE-CUT KIT:

A weather tight shell. The PCK is the complete kit for a design. It includes everything required to assemble the building shell and includes doors and windows.



Configure Yours at
WWW.JAMAICACOTTAGESHOP.COM



8X14 THREE SLED SHED COMPLETE PRE-CUT KIT

Base Area: 112 sq. ft.
Total Interior Area: 112 sq. ft.
Recommended Foundation:
6–8" Crushed Gravel
Overall Dimensions: 10'6"H
x 15'2"W x 9'2"D
Estimated Weight: 5000 lbs

Floor System

2 (qty) 4x6x14' Hemlock Skids 2"x6" rough sawn Hemlock Joists 24" On Center 34" CDX Plywood Floor Decking Floor Weight Rating: 25 lbs/sq. ft.

Walls

4"x4" Hemlock Post and Beam Wall Framing Wall Height: Front: 83" Rear: 71" Siding: 1" rough sawn Pine Board & Batten 1" rough sawn Pine Corner & Door Trim & 2" rough sawn

Pine Fascia & Shadow Trim

The 8x14 Three Sled Shed includes three sliding barn doors and a wood louvered vent. Note: Pictures may reflect client upgrades and modifications that do not come standard.

Roof

Saltbox Roof Style
Roof Pitch: Front: 12/12 Rear: 6/12
2"x6" rough sawn Hemlock
Rafters 24" On Center
1"x6" rough sawn Hemlock
Exposed Collar Ties
1"x4" rough sawn Hemlock
Strapping 20" On Center
Corrugated 29g Metal
Roofing, Color: Evergreen

Door

3 (qty) 4-0 JCS-built 2"Thick rough sawn Pine Sliding Barn Doors: w/ 3x14 Pressure Treated Ramp Additional Features 1 (qty) Wood Louvered Vent

Assembly & Logistics Information

Estimated Assembly Time: Two People: 24 hrs Estimated Shipping Cube Sizes

Cube 1: 42"x48"x168" Cube 2: 42"x32"x168"

3SLDSHD.8X14.PCK