


This Run In includes all of the bells and whistles for a livestock shelter. A kickplate conserves the siding, steel corner brackets and pressure treated sill plate allow the building to be pulled around a pasture and battens provide additional protection from wind and rain.



FULLY ASSEMBLED:

A weather tight shell. Specifications are the same as a PCK. Fully assembled prefabricated sheds and cottage buildings deliver exclusively to the northeast USA.



Additional Sizes:

8X10|8X12|8X14|8X16|8X20 10X10|10X12|10X14|10X16|10X18|10X20| 12X12|12X14|12X16|12X18|12X20|

Additional Types: FRAME ONLY KIT | COMPLETE KIT |

Configure Yours at
WWW.JAMAICACOTTAGESHOP.COM



10X10 RUN-IN STANDARD FULLY ASSEMBLED

Base Area: 100 sq. ft.

Total Interior Area: 100 sq. ft. Recommended Foundation:

4–6" Crushed Gravel

Overall Dimensions: 10'6"H x 11'2"W x 11'8"D

Estimated Weight: 3700 lbs

Sill Plates

4x6 Treated Sill Plate

Walls

4"x4" Hemlock Post and Beam Wall Framing

Wall Height: Front: 90" Rear: 70"

Siding: 1" rough sawn Pine Board & Batten

1" rough sawn Pine Corner & Door Trim & 2" rough sawn Pine Fascia & Shadow Trim

Roof

Saltbox Roof Style Roof Pitch: Front: 10/12 Rear: 6/12 The fully assembled unit includes a treated sill plate and hemlock framing, pine board and batten siding, and a corrugated metal roof along with kick plate and steel brackets. Note: Pictures may reflect client upgrades and modifications that do not come standard.

2"x6" rough sawn Hemlock Rafters 24" On Center

1"x6" rough sawn Hemlock Exposed Collar Ties

1"x4" rough sawn Hemlock Strapping 20" On Center

Corrugated 29g Metal Roofing, Color: Evergreen

6" Front & Gable & 14" Rear Overhangs

Rough Opening:

1 (qty) 64"W x 76"H

Additional Features

Heavy Duty Steel Corner Brackets Solid Hemlock 36" Kick Plate around Interior

Delivery & Logistics Information

Fully Assembled prefabricated sheds and cottage buildings are deliverable exclusively to the Northeast USA.

RIST.10X10.FA