


This Run In includes all of the bells and whistles for a livestock shelter. A kickplate conserves the siding, steel corner brackets and pressure treated sill plate allow the building to be pulled around a pasture and battens provide additional protection from wind and rain.



COMPLETE PRE-CUT KIT:

A weather tight shell. The PCK is the complete kit for a design. It includes everything required to assemble the building shell and includes doors and windows.



Step-by-Step Instructions
 & All Fastening Hardware Included

Additional Sizes:

8X10 | 8X12 | 8X14 | 8X16 | 8X20 10X10 | 10X12 | 10X14 | 10X16 | 10X18 | 10X20 | 12X12 | 12X14 | 12X16 | 12X18 | 12X20 |

Additional Types:

FRAME ONLY KIT | COMPLETE KIT |
FULLY ASSEMBLED

Configure Yours at
WWW.JAMAICACOTTAGESHOP.COM



10X14 RUN-IN STANDARD COMPLETE PRE-CUT KIT

Base Area: 140 sq. ft.

Total Interior Area: 140 sq. ft.

Recommended Foundation:

4–6" Crushed Gravel

Overall Dimensions: 10'6"H

x 15′2″W x 11′8″D

Estimated Weight: 4000 lbs

Sill Plates

4x6 Treated Sill Plate

Walls

4"x4" Hemlock Post and Beam Wall Framing

Wall Height: Front: 90" Rear: 70"

Siding: 1" rough sawn Pine Board & Batten

1" rough sawn Pine Corner & Door Trim & 2" rough sawn Pine Fascia & Shadow Trim

Roof

Saltbox Roof Style

Roof Pitch: Front: 10/12 Rear: 6/12

The complete pre-cut kit includes a treated sill plate and hemlock framing, pine board and batten siding, and a corrugated metal roof. Note: Pictures may reflect client upgrades and modifications that do not come standard.

2"x6" rough sawn Hemlock Rafters 24" On Center

1"x6" rough sawn Hemlock Exposed Collar Ties

1"x4" rough sawn Hemlock Strapping 20" On Center

Corrugated 29g Metal Roofing, Color: Evergreen

6" Front & Gable & 14" Rear Overhangs

Rough Opening:

1 (qty) 112"W x 76"H

Additional Features

Heavy Duty Steel Corner Brackets Solid Hemlock 36" Kick Plate around Interior

Assembly & Logistics Information

Estimated Assembly Time: Two People: 24 hrs

Estimated Shipping Cube Sizes

Cube 1: 42"x48"x168"

RIST.10X14.PCK